



TGIK.R20739 Roofing Systems, Uplift Resistance

[Page Bottom](#)

Roofing Systems, Uplift Resistance

[See General Information for Roofing Systems, Uplift Resistance](#)

ADCO PRODUCTS INC

17340 MUNN RD
CHAGRIN FALLS, OH 44023 USA

R20739

COMBINATION HOT AND COLD SYSTEMS

1. Uplift Resistance — 120 psf.

Deck: — Steel, min 22 MSG

Barrier Board: — Min. thickness 1/2 in. G-P Gypsum DensDeck® or any other UL Classified gypsum wallboard, adhered to the deck with "Millenium Pourable Foam Insulation Adhesive," 3/4 gal. / sq.

Insulation: — Any UL Classified High Density Fiberboard, min. thickness 1 in., adhered to the barrier board with "Millenium Pourable Foam Insulation Adhesive," 3/4 gal. / sq.

Membrane: — Any UL Classified, hot mopped or torch applied modified bitumen membrane system, hot mopped or cold applied built-up system (see Roofing Systems, TGFU).

2. Uplift Resistance: — 90 psf

Deck: — Steel, min 22 MSG

Insulation: — Any UL Classified polyisocyanurate, min. thickness 1.2 in., adhered to the deck with "Millenium Pourable Foam Insulation Adhesive," .38 gal. / sq.

Insulation (Optional): — Any UL Classified High Density fiberboard, min. thickness 1 in., adhered to the barrier board with "Millenium Pourable Foam Insulation Adhesive," 3/4 gal. / sq.

Membrane: — Any UL Classified, hot mopped or torch applied modified bitumen membrane system, hot mopped or cold applied built-up system (see Roofing Systems, TGFU).

3. Uplift Resistance: — 90 psf

Deck: — Steel, min 22 MSG

Barrier Board (Optional): — Min. thickness 1/2 in. G-P Gypsum DensDeck® or any other UL Classified gypsum wallboard, adhered to the deck with "Millenium Pourable Foam Insulation Adhesive," 3/4 gal. / sq.

Insulation (Optional): — Any UL Classified polyisocyanurate, min. thickness 1.2 in., adhered to the deck with "Millenium Pourable Foam Insulation Adhesive," 3/4 gal. / sq.

Insulation: — Any UL Classified High Density fiberboard, min. thickness 1 in., adhered to the barrier board with "Millenium Pourable Foam Insulation Adhesive," 3/4 gal. / sq.

Membrane: — Any UL Classified, hot mopped or torch applied modified bitumen membrane system, hot mopped or cold applied built-up system (see Roofing Systems, TGFU).

[Last Updated](#) on 2009-12-30

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

